

Flash Lighting Kit Setup Instructions

This document contains step-by-step instructions for setting up one of our flash lighting kits. Your kit should include:

- One (1) light stand
- One (1) mono light
- One (1) hot shoe sync cord
- One (1) power cord
- One (1) softbox tent
- One (1) front diffuser panel
- One (1) inner diffuser panel
- Four (4) flex rods
- One (1) spring ring
- One (1) carrying case for softbox
- One (1) carrying case for lighting kit



Figure 1

The exact contents of your kit may vary based upon your order. Refer to Figure 1 for the items included in the instructional kit.



Figure 2




Figure 3




Figure 4



Figure 5

Step 1: Remove the protective cap from the top of the light stand as shown in Figure 2.

Step 2: Loosen the wing nut at the top of the light stand legs by turning counterclockwise as shown in Figure 3. Expand the legs so that the light stand will stand up on its own, and then tighten the wing nut.

Step 3: Open the flip locks on the light stand joints to allow the light stand sections to move freely. Raise and lower the sections of the stand to the desired height, and close the flip locks to hold the sections in place. Refer to Figure 4 for a detailed look at these locks.

At this point, the light should stand on its own at your desired height, as illustrated in Figure 5.




Figure 6




Figure 7

Step 4: Mount the mono on the light stand. Start by loosening the screw at the base of the mono light. Slide the mono light onto the tip of the light stand and tighten the screw until the mono light fits securely as shown in Figure 6.

Step 5: Adjust the angle of the mono light by loosening the screw on the side as shown in Figure 7. Swivel the light to the desired angle, then retighten the screw.



Your assembly should then look like Figure 8.




Figure 9




Figure 10




Figure 11




Figure 12

Step 6: Place the spring ring square side up on a large, flat surface as shown in Figure 9.

Step 7: Arrange the softbox tent silver side down over the spring ring. Stretch the elastic center of the softbox tent around the spring ring until it fits around the square part of the spring ring and above the circular bottom. Refer to Figure 10 for a look at this completed step.

Step 8: Flip the spring ring and softbox tent assembly over so that the silver side of the softbox and circular side of the spring ring is visible.

Step 9: Insert the plain end of one flex rod into a slot in the spring ring. Insert the other end (with a silver cap) into the pocket located on one corner of the softbox tent as shown in Figure 11.

Repeat step 4 three more times until all rods are inserted. Refer to Figure 12 and Figure 13 for details. When completed, the assembly should form a box with the spring ring on the surface and the corners of the softbox tent raised above the surface.



Figure 13



Figure 14

Step 10: Attach the inner diffuser panel at each corner of the softbox tent as shown in Figure 14.

Step 11: Arrange the front diffuser panel around the softbox tent as illustrated in Figure 15. Use the Velcro fasteners to securely attach the panel to the softbox tent.



Figure 15




Figure 16



Figure 17



Figure 18



Figure 19

Step 12: Adjust the four screws on the outside of the softbox to approximately the size of the light you are mounting the softbox on. Slide the softbox onto the light as shown in Figure 16.

Step 13: Tighten the screws until the softbox is secure. Your softbox and mono light should now look like Figure 18.

Step 14: Plug the sync cord and power cord into the back on the mono light as shown in Figure 19.

Once fully assembled, your flash lighting kit should match that in Figure 20.



Figure 20

Cowboystudio